FIREPROOFING PLASTER MACHINE

TURBOMIX

CATALOG

- TURBOMIX GLOBAL -

QUALITY

We have been providing good service for many years with our 100% international products and world class machine and spare parts quality as a plastering machine manufacturer.

Turbomix embraces the highest standards in areas such as quality, environmental protection, occupational health, and customer satisfaction in the plastering machines it produces. As a concrete demonstration of this approach, its international certifications demonstrate its reliability and professionalism in the sector.

CE

ISO 10002:2018

ISO 9001:2015

ISO 45001:2018

ISO 14001:2015

TECHNICAL SPECIFICATIONS

- **Pumping capacity:** 70 l/min
- **Pumping capacity (with a different pump):** 140 l/min
- **Stator rotor set:** 2L6, 2L6 Plus, 2L6 Plus with clamp
- **Pumping pressure:** 25 bar
- **Pumping distance (horizontal):** 110 m (max)
- **Pumping height:** 45 m (max)
- **Power supply:** 400 V, 50 Hz
- **Pumping motor:** 7.50 KW
- **Mixing motor:** 3.00 KW
- **Electrical cable:** 5*4 mm² TTR, 25 m
- **Protection fuse:** 3*40 A
- **Compressor:** 2.20 KW, 400 l/min, 8 bar
- **Hopper capacity:** 180 l
- **Length:** 2700 mm
- **Width:** 1400 mm
- **Height:** 1650 mm
- **Transport height:** 1650 mm
- **Weight:** 855 kg

SKU: 10-01-1329

TURBOMIX 70 FPM FIREPROOFING PLASTER MACHINE

STANDARD EQUIPMENT

- **Stator rotor set:** 2L6
- **Mortar hose:** 40 bar, Ø 35 mm, 20 m, coupling
- **Mortar hose:** 40 bar, Ø 35 mm, 10 m, coupling
- **Mortar hose:** 40 bar, Ø 35 mm, 10 m, rotating coupling
- **Mortar hose reduction:** 50/35 mm
- **Mortar hose reduction:** 35/25 mm (optional)
- **Mortar hose gasket:** Ø 35 mm, 4 piece
- **Manometer:** 60 bar
- **Vibrating screen:** 6 mm
- **Air hose:** Ø 10 mm, 20 m, geka coupling
- **Air hose:** Ø 10 mm, 11 m, geka coupling
- **Air hose:** Ø 10 mm, 10 m, geka coupling
- **Air hose gasket:** 10 mm, 2 piece
- **Spray gun:** Ø 35 mm, Nozzle 12 mm
- **Spray gun:** Ø 25 mm, Nozzle 12 mm (optional)
- **Nozzle:** 12 mm, 2 piece
- **Electrical cable:** 5*4 mm^2 TTR, 25 m
- **Sponge ball:** Ø 35 mm, 3 piece
- **Compressor:** 2.20 KW, 400 l/min
- Control panel
- Coupling
- Cleaning rod
- Manual rotor dismantling apparatus
- Vehicle towing unit
- GPS (optional)

APPLICATION AREAS

- All fire resistant mortars

SKU: 10-01-1329

TURBOMIX 70 FPM FIREPROOFING PLASTER MACHINE

TECHNICAL SPECIFICATIONS

- **Pumping capacity:** 10-70 l/min
- **Pumping capacity (with a different pump):** 10-140 l/min
- **Stator rotor set:** 2L6, 2L6 Plus, 2L6 Plus with clamp
- **Pumping pressure:** 25 bar
- **Pumping distance (horizontal):** 110 m (max)
- **Pumping height:** 45 m (max)
- **Power supply:** 400 V, 50 Hz
- **Pumping motor:** 7.50 KW
- **Mixing motor:** 3.00 KW
- **Electrical cable:** 5*4 mm² TTR, 25 m
- **Protection fuse:** 3*40 A
- **Compressor:** 2.20 KW, 400 l/min, 8 bar
- **Hopper capacity:** 180 l
- **Length:** 2700 mm
- **Width:** 1400 mm
- **Height:** 1650 mm
- **Transport height:** 1650 mm
- **Weight:** 860 kg

SKU: 10-01-1330

TURBOMIX 70 FC FPM FIREPROOFING PLASTER MACHINE

STANDARD EQUIPMENT

- **Stator rotor set:** 2L6
- **Mortar hose:** 40 bar, Ø 35 mm, 20 m, coupling
- **Mortar hose:** 40 bar, Ø 35 mm, 10 m, coupling
- **Mortar hose:** 40 bar, Ø 35 mm, 10 m, rotating coupling
- **Mortar hose reduction:** 50/35 mm
- **Mortar hose reduction:** 35/25 mm (optional)
- **Mortar hose gasket:** Ø 35 mm, 4 piece
- **Manometer:** 60 bar
- **Vibrating screen:** 6 mm
- **Air hose:** Ø 10 mm, 20 m, geka coupling
- **Air hose:** Ø 10 mm, 11 m, geka coupling
- **Air hose:** Ø 10 mm, 10 m, geka coupling
- **Air hose gasket:** 10 mm, 2 piece
- **Spray gun:** Ø 35 mm, Nozzle 12 mm
- **Spray gun:** Ø 25 mm, Nozzle 12 mm (optional)
- **Nozzle:** 12 mm, 2 piece
- **Electrical cable:** 5*4 mm^2 TTR, 25 m
- **Sponge ball:** Ø 35 mm, 3 piece
- **Compressor:** 2.20 KW, 400 l/min
- Spray Speed Adjustment Button (Potentiometer)
- Control panel
- Coupling
- Cleaning rod
- Manual rotor dismantling apparatus
- Vehicle towing unit
- GPS (optional)

APPLICATION AREAS

- All fire resistant mortars

SKU: 10-01-1330

TURBOMIX 70 FC FPM FIREPROOFING PLASTER MACHINE

TECHNICAL SPECIFICATIONS

- **Pumping capacity:** 70 l/min
- **Pumping capacity (with a different pump):** 140 l/min
- **Stator rotor set:** 2L6, 2L6 Plus, 2L6 Plus with clamp
- **Pumping pressure:** 25 bar
- **Pumping distance (horizontal):** 110 m (max)
- **Pumping height:** 45 m (max)
- **Power supply:** 400 V, 50 Hz
- **Pumping motor:** 7.50 KW
- **Mixing motor:** 3.00 KW
- **Electrical cable:** 5*4 mm² TTR, 25 m
- **Protection fuse:** 3*40 A
- **Compressor:** 2.20 KW, 400 l/min, 8 bar
- **Hopper capacity:** 180 l
- **Length:** 2700 mm
- **Width:** 1400 mm
- **Height:** 1650 mm
- **Transport height:** 1650 mm
- **Weight:** 875 kg

SKU: 10-01-1332

TURBOMIX 70 S FPM FIREPROOFING PLASTER MACHINE

STANDARD EQUIPMENT

- **Stator rotor set:** 2L6
- **Mortar hose:** 40 bar, Ø 35 mm, 20 m, coupling
- **Mortar hose:** 40 bar, Ø 35 mm, 10 m, coupling
- **Mortar hose:** 40 bar, Ø 35 mm, 10 m, rotating coupling
- **Mortar hose reduction:** 50/35 mm
- **Mortar hose reduction:** 35/25 mm (optional)
- **Mortar hose gasket:** Ø 35 mm, 4 piece
- **Manometer:** 60 bar
- **Vibrating screen:** 6 mm
- **Air hose:** Ø 10 mm, 20 m, geka coupling
- **Air hose:** Ø 10 mm, 11 m, geka coupling
- **Air hose:** Ø 10 mm, 10 m, geka coupling
- **Air hose gasket:** 10 mm, 2 piece
- **Spray gun:** Ø 35 mm, Nozzle 12 mm
- **Spray gun:** Ø 25 mm, Nozzle 12 mm (optional)
- **Nozzle:** 12 mm, 2 piece
- **Electrical cable:** 5*4 mm^2 TTR, 25 m
- **Sponge ball:** Ø 50 mm, 2 piece
- **Compressor:** 2.20 KW, 400 l/min
- **Washing gun:** 110 cm, triggerous, dirty water filter
- **Washing Gun Hose:** 7 m, 350 bar (max)
- **Washing Motor:** 5.50 KW, 200 bar (max)
- Control panel
- Coupling
- Cleaning rod
- Manual rotor dismantling apparatus
- Vehicle towing unit
- GPS (optional)

APPLICATION AREAS

- All fire resistant mortars

SKU: 10-01-1332

TURBOMIX 70 S FPM FIREPROOFING PLASTER MACHINE

TECHNICAL SPECIFICATIONS

- **Pumping capacity:** 10-70 l/min
- **Pumping capacity (with a different pump):** 10-140 l/min
- **Stator rotor set:** 2L6, 2L6 Plus, 2L6 Plus with clamp
- **Pumping pressure:** 25 bar
- **Pumping distance (horizontal):** 110 m (max)
- **Pumping height:** 45 m (max)
- **Power supply:** 400 V, 50 Hz
- **Pumping motor:** 7.50 KW
- **Mixing motor:** 3.00 KW
- **Electrical cable:** 5*4 mm² TTR, 25 m
- **Protection fuse:** 3*40 A
- **Compressor:** 2.20 KW, 400 l/min, 8 bar
- **Hopper capacity:** 180 l
- **Length:** 2700 mm
- **Width:** 1400 mm
- **Height:** 1650 mm
- **Transport height:** 1650 mm
- **Weight:** 880 kg

SKU: 10-01-1333

TURBOMIX 70 S FC FPM FIREPROOFING PLASTER MACHINE

STANDARD EQUIPMENT

- **Stator rotor set:** 2L6
- **Mortar hose:** 40 bar, Ø 35 mm, 20 m, coupling
- **Mortar hose:** 40 bar, Ø 35 mm, 10 m, coupling
- **Mortar hose:** 40 bar, Ø 35 mm, 10 m, rotating coupling
- **Mortar hose reduction:** 50/35 mm
- **Mortar hose reduction:** 35/25 mm (optional)
- **Mortar hose gasket:** Ø 35 mm, 4 piece
- **Manometer:** 60 bar
- **Vibrating screen:** 6 mm
- **Air hose:** Ø 10 mm, 20 m, geka coupling
- **Air hose:** Ø 10 mm, 11 m, geka coupling
- **Air hose:** Ø 10 mm, 10 m, geka coupling
- **Air hose gasket:** 10 mm, 2 piece
- **Spray gun:** Ø 35 mm, Nozzle 12 mm
- **Spray gun:** Ø 25 mm, Nozzle 12 mm (optional)
- **Nozzle:** 12 mm, 2 piece
- **Electrical cable:** 5*4 mm^2 TTR, 25 m
- **Sponge ball:** Ø 50 mm, 2 piece
- **Compressor:** 2.20 KW, 400 l/min
- **Washing gun:** 110 cm, triggerous, dirty water filter
- **Washing Gun Hose:** 7 m, 350 bar (max)
- **Washing Motor:** 5.50 KW, 200 bar (max)
- Spray Speed Adjustment Button (Potentiometer)
- Control panel
- Coupling
- Cleaning rod
- Manual rotor dismantling apparatus
- Vehicle towing unit
- GPS (optional)

APPLICATION AREAS

- All fire resistant mortars

SKU: 10-01-1333

TURBOMIX 70 S FC FPM FIREPROOFING PLASTER MACHINE

TECHNICAL SPECIFICATIONS

- **Pumping capacity:** 70 l/min
- **Pumping capacity (with a different pump):** 140 l/min
- **Stator rotor set:** 2L6, 2L6 Plus, 2L6 Plus with clamp
- **Pumping pressure:** 25 bar
- **Pumping distance (horizontal):** 110 m (max)
- **Pumping height:** 45 m (max)
- **Power supply:** 400 V, 50 Hz
- **Pumping motor:** 7.50 KW
- **Mixing motor:** 3.00 KW
- **Electrical cable:** 5*4 mm² TTR, 25 m
- **Protection fuse:** 3*40 A
- **Compressor:** 2.20 KW, 400 l/min, 8 bar
- **Hopper capacity:** 180 l
- **Length:** 2700 mm
- **Width:** 1400 mm
- **Height:** 1650 mm
- **Transport height:** 1650 mm
- **Weight:** 885 kg

SKU: 10-01-1336

TURBOMIX 70 S/Y FPM FIREPROOFING PLASTER MACHINE

STANDARD EQUIPMENT

- **Stator rotor set:** 2L6
- **Mortar hose:** 40 bar, Ø 35 mm, 20 m, coupling
- **Mortar hose:** 40 bar, Ø 35 mm, 10 m, coupling
- **Mortar hose:** 40 bar, Ø 35 mm, 10 m, rotating coupling
- **Mortar hose reduction:** 50/35 mm
- **Mortar hose reduction:** 35/25 mm (optional)
- **Mortar hose gasket:** Ø 35 mm, 4 piece
- **Manometer:** 60 bar
- **Vibrating screen:** 6 mm
- **Air hose:** Ø 10 mm, 20 m, geka coupling
- **Air hose:** Ø 10 mm, 11 m, geka coupling
- **Air hose:** Ø 10 mm, 10 m, geka coupling
- **Air hose gasket:** 10 mm, 2 piece
- **Spray gun:** Ø 35 mm, Nozzle 12 mm
- **Spray gun:** Ø 25 mm, Nozzle 12 mm (optional)
- **Nozzle:** 12 mm, 2 piece
- **Electrical cable:** 5*4 mm^2 TTR, 25 m
- **Sponge ball:** Ø 50 mm, 2 piece
- **Compressor:** 2.20 KW, 400 l/min
- **Washing gun:** 110 cm, triggerous, dirty water filter
- **Washing Gun Hose:** 7 m, 350 bar (max)
- **Washing Motor:** 5.50 KW, 200 bar (max)
- Automatic Greasing System
- Control panel
- Coupling
- Cleaning rod
- Manual rotor dismantling apparatus
- Vehicle towing unit
- GPS (optional)

APPLICATION AREAS

- All fire resistant mortars

SKU: 10-01-1336

TURBOMIX 70 S/Y FPM FIREPROOFING PLASTER MACHINE

TECHNICAL SPECIFICATIONS

- **Pumping capacity:** 10-70 l/min
- **Pumping capacity (with a different pump):** 10-140 l/min
- **Stator rotor set:** 2L6, 2L6 Plus, 2L6 Plus with clamp
- **Pumping pressure:** 25 bar
- **Pumping distance (horizontal):** 110 m (max)
- **Pumping height:** 45 m (max)
- **Power supply:** 400 V, 50 Hz
- **Pumping motor:** 7.50 KW
- **Mixing motor:** 3.00 KW
- **Electrical cable:** 5*4 mm² TTR, 25 m
- **Protection fuse:** 3*40 A
- **Compressor:** 2.20 KW, 400 l/min, 8 bar
- **Hopper capacity:** 180 l
- **Length:** 2700 mm
- **Width:** 1400 mm
- **Height:** 1650 mm
- **Transport height:** 1650 mm
- **Weight:** 890 kg

SKU: 10-01-1337

TURBOMIX 70 S/Y FC FPM FIREPROOFING PLASTER MACHINE

STANDARD EQUIPMENT

- **Stator rotor set:** 2L6
- **Mortar hose:** 40 bar, Ø 35 mm, 20 m, coupling
- **Mortar hose:** 40 bar, Ø 35 mm, 10 m, coupling
- **Mortar hose:** 40 bar, Ø 35 mm, 10 m, rotating coupling
- **Mortar hose reduction:** 50/35 mm
- **Mortar hose reduction:** 35/25 mm (optional)
- **Mortar hose gasket:** Ø 35 mm, 4 piece
- **Manometer:** 60 bar
- **Vibrating screen:** 6 mm
- **Air hose:** Ø 10 mm, 20 m, geka coupling
- **Air hose:** Ø 10 mm, 11 m, geka coupling
- **Air hose:** Ø 10 mm, 10 m, geka coupling
- **Air hose gasket:** 10 mm, 2 piece
- **Spray gun:** Ø 35 mm, Nozzle 12 mm
- **Spray gun:** Ø 25 mm, Nozzle 12 mm (optional)
- **Nozzle:** 12 mm, 2 piece
- **Electrical cable:** 5*4 mm^2 TTR, 25 m
- **Sponge ball:** Ø 50 mm, 2 piece
- **Compressor:** 2.20 KW, 400 l/min
- **Washing gun:** 110 cm, triggerous, dirty water filter
- **Washing Gun Hose:** 7 m, 350 bar (max)
- **Washing Motor:** 5.50 KW, 200 bar (max)
- Automatic Greasing System
- Spray Speed Adjustment Button (Potentiometer)
- Control panel
- Coupling
- Cleaning rod
- Manual rotor dismantling apparatus
- Vehicle towing unit
- GPS (optional)

APPLICATION AREAS

- All fire resistant mortars

SKU: 10-01-1337

TURBOMIX 70 S/Y FC FPM FIREPROOFING PLASTER MACHINE

TECHNICAL SPECIFICATIONS

- **Pumping capacity:** 70 l/min
- **Pumping capacity (with a different pump):** 140 l/min
- **Stator rotor set:** 2L6, 2L6 Plus, 2L6 Plus with clamp
- **Pumping pressure:** 25 bar
- **Pumping distance (horizontal):** 110 m (max)
- **Pumping height:** 45 m (max)
- **Power supply:** 400 V, 50 Hz
- **Pumping motor:** 7.50 KW
- **Mixing motor:** 3.00 KW
- **Electrical cable:** 5*4 mm^2 TTR, 25 m
- **Protection fuse:** 3*40 A
- **Compressor:** 2.20 KW, 400 l/min, 8 bar
- **Hopper capacity:** 180 l
- **Length:** 2700 mm
- **Width:** 1400 mm
- **Height:** 1650 mm
- **Transport height:** 1650 mm
- **Weight:** 865 kg

SKU: 10-01-1339

TURBOMIX 70 Y FPM FIREPROOFING PLASTER MACHINE

STANDARD EQUIPMENT

- **Stator rotor set:** 2L6
- **Mortar hose:** 40 bar, Ø 35 mm, 20 m, coupling
- **Mortar hose:** 40 bar, Ø 35 mm, 10 m, coupling
- **Mortar hose:** 40 bar, Ø 35 mm, 10 m, rotating coupling
- **Mortar hose reduction:** 50/35 mm
- **Mortar hose reduction:** 35/25 mm (optional)
- **Mortar hose gasket:** Ø 35 mm, 4 piece
- **Manometer:** 60 bar
- **Vibrating screen:** 6 mm
- **Air hose:** Ø 10 mm, 20 m, geka coupling
- **Air hose:** Ø 10 mm, 11 m, geka coupling
- **Air hose:** Ø 10 mm, 10 m, geka coupling
- **Air hose gasket:** 10 mm, 2 piece
- **Spray gun:** Ø 35 mm, Nozzle 12 mm
- **Spray gun:** Ø 25 mm, Nozzle 12 mm (optional)
- **Nozzle:** 12 mm, 2 piece
- **Electrical cable:** 5*4 mm² TTR, 25 m
- **Sponge ball:** Ø 35 mm, 3 piece
- **Compressor:** 2.20 KW, 400 l/min
- Automatic Greasing System
- Control panel
- Coupling
- Cleaning rod
- Manual rotor dismantling apparatus
- Vehicle towing unit
- GPS (optional)

APPLICATION AREAS

- All fire resistant mortars

SKU: 10-01-1339

TURBOMIX 70 Y FPM FIREPROOFING PLASTER MACHINE

TECHNICAL SPECIFICATIONS

- **Pumping capacity:** 10-70 l/min
- **Pumping capacity (with a different pump):** 10-140 l/min
- **Stator rotor set:** 2L6, 2L6 Plus, 2L6 Plus with clamp
- **Pumping pressure:** 25 bar
- **Pumping distance (horizontal):** 110 m (max)
- **Pumping height:** 45 m (max)
- **Power supply:** 400 V, 50 Hz
- **Pumping motor:** 7.50 KW
- **Mixing motor:** 3.00 KW
- **Electrical cable:** 5*4 mm² TTR, 25 m
- **Protection fuse:** 3*40 A
- **Compressor:** 2.20 KW, 400 l/min, 8 bar
- **Hopper capacity:** 180 l
- **Length:** 2700 mm
- **Width:** 1400 mm
- **Height:** 1650 mm
- **Transport height:** 1650 mm
- **Weight:** 870 kg

SKU: 10-01-1340

TURBOMIX 70 Y FC FPM FIREPROOFING PLASTER MACHINE

STANDARD EQUIPMENT

- **Stator rotor set:** 2L6
- **Mortar hose:** 40 bar, Ø 35 mm, 20 m, coupling
- **Mortar hose:** 40 bar, Ø 35 mm, 10 m, coupling
- **Mortar hose:** 40 bar, Ø 35 mm, 10 m, rotating coupling
- **Mortar hose reduction:** 50/35 mm
- **Mortar hose reduction:** 35/25 mm (optional)
- **Mortar hose gasket:** Ø 35 mm, 4 piece
- **Manometer:** 60 bar
- **Vibrating screen:** 6 mm
- **Air hose:** Ø 10 mm, 20 m, geka coupling
- **Air hose:** Ø 10 mm, 11 m, geka coupling
- **Air hose:** Ø 10 mm, 10 m, geka coupling
- **Air hose gasket:** 10 mm, 2 piece
- **Spray gun:** Ø 35 mm, Nozzle 12 mm
- **Spray gun:** Ø 25 mm, Nozzle 12 mm (optional)
- **Nozzle:** 12 mm, 2 piece
- **Electrical cable:** 5*4 mm^2 TTR, 25 m
- **Sponge ball:** Ø 35 mm, 3 piece
- **Compressor:** 2.20 KW, 400 l/min
- Automatic Greasing System
- Spray Speed Adjustment Button (Potentiometer)
- Control panel
- Coupling
- Cleaning rod
- Manual rotor dismantling apparatus
- Vehicle towing unit
- GPS (optional)

APPLICATION AREAS

- All fire resistant mortars

SKU: 10-01-1340

TURBOMIX 70 Y FC FPM FIREPROOFING PLASTER MACHINE

TURBOMIX

+90 543 310 95 95

info@turbomixmachinery.com

Ferhatpaşa Mah. G.9 Sk. No:20
34888 Ataşehir / Istanbul / Türkiye

www.turbomixmachinery.com