

**GYPSUM
PLASTER
MACHINES**





- TURBOMIX GLOBAL -

QUALITY

We have been providing good service for many years with our 100% international products and world class machine and spare parts quality as a plastering machine manufacturer.

Turbomix embraces the highest standards in areas such as quality, environmental protection, occupational health, and customer satisfaction in the plastering machines it produces. As a concrete demonstration of this approach, its international certifications demonstrate its reliability and professionalism in the sector.



CE



ISO 10002:2018



ISO 9001:2015



ISO 45001:2018



ISO 14001:2015

TECHNICAL SPECIFICATIONS

- **Pumping capacity:** 27 l/min
- **Pumping capacity (with a different pump):** 32 l/min
- **Stator rotor set:** D6-3, D7-2.5, D8-2
- **Pumping pressure:** 30 bar
- **Pumping distance (horizontal):** 40 m (max)
- **Power supply:** 380 V, 50 Hz
- **Pumping motor:** 5.50 kW
- **Mixing motor:** 0.55 kW
- **Electrical cable:** 5*4 mm² TTR, 25 m
- **Protection fuse:** 3*32 A
- **Water pump:** 0.50 HP
- **Water connection:** 3/4"
- **Compressor:** 0.90 kW, 250 l/min, 6 bar
- **Hopper capacity:** 150 l
- **Length:** 1250 mm
- **Width:** 750 mm
- **Height:** 1620 mm
- **Transport height:** 950 mm
- **Weight:** 320 kg



SKU: 11-01-1007

TURBOMIX PLUS GYPSUM PLASTER MACHINE

STANDARD EQUIPMENT

- **Stator rotor set:** D6-3
- **Mortar hose:** 40 bar, Ø 25 mm, 15 m, coupling
- **Mortar hose gasket:** 25 mm, 2 piece
- **Air hose:** Ø 10 mm, 16 m, geka coupling
- **Water hose:** 3/4", 5 m
- **Water pump:** 0.50 HP
- **Flowmeter:** 150 - 1500 l/h
- **Spray gun:** Ø 25 mm, Nozzle 14 mm
- **Nozzle:** 14 mm, 1 piece
- **Electrical cable:** 5*4 mm² TTR, 25 m
- **Sponge ball:** Ø 30 mm, 2 piece
- **Compressor:** 0.90 kW, 250 l/min, 6 bar
- Control Panel
- Cleaning rod
- Mixer shaft
- Manual rotor dismantling apparatus

APPLICATION AREAS

- Gypsum based mortars
- Injection mortars
- Reinforcement and adhesive mortars
- Self spread screeds
- Lime - gypsum mortars
- Cement mortars
- Lime mortars
- Lime - cement mortars
- Fango materials
- Insulation plasters
- Embedment mortars
- Exterior base coat plasters
- Surface screeds
- Wall mortars
- Premix mortars (Pre mixed bag)
- Insulation materials

SKU: 11-01-1007

TURBOMIX PLUS GYPSUM PLASTER MACHINE

TECHNICAL SPECIFICATIONS

- **Pumping capacity:** 32 l/min
- **Pumping capacity (with a different pump):** 32 l/min
- **Stator rotor set:** D6-3, D7-2.5, D8-2
- **Pumping pressure:** 30 bar
- **Pumping distance (horizontal):** 50 m (max)
- **Power supply:** 380 V, 50 Hz
- **Pumping motor:** 5.50 kW
- **Mixing motor:** 0.55 kW
- **Electrical cable:** 5*4 mm² TTR, 30 m
- **Protection fuse:** 3*32 A
- **Water pump:** 1.00 HP
- **Water connection:** 3/4"
- **Compressor:** 0.90 kW, 250 l/min, 6 bar
- **Hopper capacity:** 150 l
- **Length:** 1250 mm
- **Width:** 750 mm
- **Height:** 1620 mm
- **Transport height:** 950 mm
- **Weight:** 330 kg



SKU: 11-01-1009

TURBOMIX TITAN GYPSUM PLASTER MACHINE

STANDARD EQUIPMENT

- **Stator rotor set:** D6-3
- **Mortar hose:** 40 bar, Ø 25 mm, 15 m, coupling
- **Mortar hose gasket:** 25 mm, 3 piece
- **Air hose:** Ø 10 mm, 16 m, geka coupling
- **Water hose:** 3/4", 7 m
- **Water pump:** 1.00 HP
- **Flowmeter:** 150 - 1500 l/h
- **Spray gun:** Ø 25 mm, Nozzle 14 mm
- **Nozzle:** 14 mm, 2 piece
- **Electrical cable:** 5*4 mm² TTR, 30 m
- **Sponge ball:** Ø 30 mm, 4 piece
- **Compressor:** 0.90 kW, 250 l/min, 6 bar
- Control Panel
- Cleaning rod
- Mixer shaft
- Manual rotor dismantling apparatus

APPLICATION AREAS

- Gypsum based mortars
- Injection mortars
- Reinforcement and adhesive mortars
- Self spread screeds
- Lime - gypsum mortars
- Cement mortars
- Lime mortars
- Lime - cement mortars
- Fango materials
- Insulation plasters
- Embedment mortars
- Exterior base coat plasters
- Surface screeds
- Wall mortars
- Premix mortars (Pre mixed bag)
- Insulation materials

SKU: 11-01-1009

TURBOMIX TITAN GYPSUM PLASTER MACHINE

TECHNICAL SPECIFICATIONS

- **Pumping capacity:** 22 l/min
- **Pumping capacity (with a different pump):** 32 l/min
- **Stator rotor set:** D6-3, D7-2.5, D8-2
- **Pumping pressure:** 20 bar
- **Pumping distance (horizontal):** 30 m (max)
- **Power supply:** 220 V, 50 Hz
- **Pumping motor:** 3.00 kW
- **Mixing motor:** 0.55 kW
- **Electrical cable:** 5*4 mm² TTR, 20 m
- **Protection fuse:** 1*32 A
- **Water pump:** 0.50 HP
- **Water connection:** 3/4"
- **Compressor:** 0.90 kW, 250 l/min, 6 bar
- **Hopper capacity:** 150 l
- **Length:** 1250 mm
- **Width:** 750 mm
- **Height:** 1620 mm
- **Transport height:** 950 mm
- **Weight:** 305 kg



SKU: 11-01-1008

TURBOMIX MONO GYPSUM PLASTER MACHINE

STANDARD EQUIPMENT

- **Stator rotor set:** D6-3
- **Mortar hose:** 40 bar, Ø 25 mm, 10 m, coupling
- **Mortar hose gasket:** 25 mm, 2 piece
- **Air hose:** Ø 10 mm, 16 m, geka coupling
- **Water hose:** 3/4", 5 m
- **Water pump:** 0.50 HP
- **Flowmeter:** 150 - 1500 l/h
- **Spray gun:** Ø 25 mm, Nozzle 14 mm
- **Nozzle:** 14 mm, 1 piece
- **Electrical cable:** 5*4 mm² TTR, 20 m
- **Sponge ball:** Ø 30 mm, 2 piece
- **Compressor:** 0.90 kW, 250 l/min, 6 bar
- Control Panel
- Cleaning rod
- Mixer shaft
- Manual rotor dismantling apparatus

APPLICATION AREAS

- Gypsum based mortars
- Injection mortars
- Reinforcement and adhesive mortars
- Self spread screeds
- Lime - gypsum mortars
- Cement mortars
- Lime mortars
- Lime - cement mortars
- Fango materials
- Insulation plasters
- Embedment mortars
- Exterior base coat plasters
- Surface screeds
- Wall mortars
- Premix mortars (Pre mixed bag)
- Insulation materials

SKU: 11-01-1008

TURBOMIX MONO GYPSUM PLASTER MACHINE

TECHNICAL SPECIFICATIONS

- **Pumping capacity:** 22 l/min
- **Pumping capacity (with a different pump):** 27 l/min
- **Stator rotor set:** D6-3, D7-2.5, D8-2
- **Pumping pressure:** 30 bar
- **Pumping distance (horizontal):** 25 m (max)
- **Power supply:** 380 V, 50 Hz
- **Pumping motor:** 5.50 kW
- **Mixing motor:** 0.55 kW
- **Electrical cable:** 5*4 mm² TTR, 15 m
- **Protection fuse:** 3*32 A
- **Water pump:** 0.50 HP
- **Water connection:** 3/4"
- **Compressor:** 0.90 kW, 250 l/min, 6 bar
- **Hopper capacity:** 125 l
- **Length:** 1200 mm
- **Width:** 700 mm
- **Height:** 1550 mm
- **Transport height:** 880 mm
- **Weight:** 270 kg



SKU: 11-01-1010

TURBOMIX ECO GYPSUM PLASTER MACHINE

STANDARD EQUIPMENT

- **Stator rotor set:** D6-3
- **Mortar hose:** 40 bar, Ø 25 mm, 10 m, coupling
- **Mortar hose gasket:** 25 mm, 1 piece
- **Air hose:** Ø 10 mm, 10 m, geka coupling
- **Water hose:** 3/4", 5 m
- **Water pump:** 0.50 HP
- **Flowmeter:** 150 - 1500 l/h
- **Spray gun:** Ø 25 mm, Nozzle 14 mm
- **Nozzle:** 14 mm, 1 piece
- **Electrical cable:** 5*4 mm² TTR, 15 m
- **Sponge ball:** Ø 30 mm, 1 piece
- **Compressor:** 0.90 kW, 250 l/min, 6 bar
- Control Panel
- Cleaning rod
- Mixer shaft
- Manual rotor dismantling apparatus

APPLICATION AREAS

- Gypsum based mortars
- Injection mortars
- Reinforcement and adhesive mortars
- Self spread screeds
- Lime - gypsum mortars
- Cement mortars
- Lime mortars
- Lime - cement mortars
- Fango materials
- Insulation plasters
- Embedment mortars
- Exterior base coat plasters
- Surface screeds
- Wall mortars
- Premix mortars (Pre mixed bag)
- Insulation materials

SKU: 11-01-1010

TURBOMIX ECO GYPSUM PLASTER MACHINE



TURBOMIX



+90 543 310 95 95



info@turbomixmachinery.com



Ferhatpaşa Mah. G.9 Sk. No:20
34888 Ataşehir / İstanbul / Türkiye



www.turbomixmachinery.com