

**PLASTER  
MACHINES**





- TURBOMIX GLOBAL



# QUALITY

Although there are many plaster and mortar machines manufacturers in the sector, we have been providing trouble-free service for many years with the quality of machinery and spare parts at world standards.

At the same time, we do not let you down with 100% customer satisfaction, with a variety of machines and spare parts tailored to your needs, to the desired performance and needs.



---

## TECHNICAL DETAILS

- **Pumping Capacity:** 20 l/min
- **Pumping Capacity with Various Pumps:** 6-35 l/min
- **Pumping Pressure:** 30 bar
- **Pumping Distance (Horizontal):** 40 m (Max)
- **Power Supply:** 220 V
- **Pumping Motor:** 5.5 kW
- **Mill Motor:** 0.55 kW
- **Power Cable:** 4\*4 mm<sup>2</sup>
- **Fuse Protection:** 3\*32 A
- **Water Supply Connection:** 3/4"
- **Compressor Capacity:** 0.9 kW, 250 l/dk
- **Remote Control:** Pneumatic
- **Mortar Hose:** Ø 25 mm
- **Hopper Capacity:** 150 l
- **Length:** 1250 mm
- **Width:** 750 mm
- **Height:** 1620 mm
- **Loading Height:** 950 mm
- **Total Weight:** 320 kg



# TURBOMIX MONO PLASTER MACHINE

---



## STANDARD EQUIPMENTS

- **Rotor&Stator:** D6-3
- **Mortar Hose:** 40 bar, Ø 25 mm, 10 m, with coupling
- **Air Hose:** 12 mm, 16 m, geka coupling
- **Water Hose:** 3/4 with clack, 7 m
- **Spray Gun:** Turnable, Ø 25 mm, Nozzle 14 mm
- **Power Cable:** 4\*6 mm<sup>2</sup> TTR, 33 m
- **Mixing Shaft**
- **2 x Cleaning Ball 30 mm**
- **Round File**
- **6 cm Scraper**
- **Wire Brush**
- **Utility Knife**
- **Manual Rotor Removal Apparatus**

# TURBOMIX MONO PLASTER MACHINE

---

## TECHNICAL DETAILS

- **Pumping Capacity:** 20 l/min
- **Pumping Capacity with Various Pumps:** 6-35 l/min
- **Pumping Pressure:** 30 bar
- **Pumping Distance (Horizontal):** 40 m (Max)
- **Power Supply:** 380 V, 50 Hz
- **Pumping Motor:** 5.5 kW
- **Mill Motor:** 0.55 kW
- **Power Cable:** 4\*4 mm<sup>2</sup>
- **Fuse Protection:** 3\*32 A
- **Water Supply Connection:** 3/4"
- **Compressor Capacity:** 0.9 kW, 250 l/dk
- **Remote Control:** Pneumatic
- **Mortar Hose:** Ø 25 mm
- **Hopper Capacity:** 150 l
- **Length:** 1250 mm
- **Width:** 750 mm
- **Height:** 1620 mm
- **Loading Height:** 950 mm
- **Total Weight:** 320 kg



# TURBOMIX TITAN PLASTER MACHINE

---



## STANDARD EQUIPMENTS

- **Rotor&Stator:** D6-3
- **Mortar Hose:** 40 bar, Ø 25 mm, 10 m, with coupling
- **Air Hose:** 12 mm, 11 m, geka coupling
- **Water Hose:** 3/4 with clack, 7 m
- **Spray Gun:** Turnable, Ø 25 mm, Nozzle 14 mm
- **Power Cable:** 3\*4 mm<sup>2</sup> TTR, 20 m
- **Mixing Shaft**
- **2 x Cleaning Ball 30 mm**
- **Round File**
- **6 cm Scraper**
- **Wire Brush**
- **Utility Knife**
- **Manual Rotor Removal Apparatus**

# TURBOMIX TITAN PLASTER MACHINE

## TECHNICAL DETAILS

- **Pumping Capacity:** 20 l/min
- **Pumping Capacity with Various Pumps:** 6-35 l/min
- **Pumping Pressure:** 30 bar
- **Pumping Distance (Horizontal):** 40 m (Max)
- **Power Supply:** 380 V, 50 Hz
- **Pumping Motor:** 5.5 kW
- **Mill Motor:** 0.55 kW
- **Power Cable:** 4\*4 mm<sup>2</sup>
- **Fuse Protection:** 3\*32 A
- **Water Supply Connection:** 3/4"
- **Compressor Capacity:** 0.9 kW, 250 l/dk
- **Remote Control:** Pneumatic
- **Mortar Hose:** Ø 25 mm
- **Hopper Capacity:** 150 l
- **Length:** 1250 mm
- **Width:** 750 mm
- **Height:** 1620 mm
- **Loading Height:** 950 mm
- **Total Weight:** 320 kg



# TURBOMIX PLUS PLASTER MACHINE





## STANDARD EQUIPMENTS

- **Rotor&Stator:** D4-1
- **Mortar Hose:** 40 bar, Ø 25 mm, 10 m, with coupling
- **Air Hose:** 12 mm, 11 m, geka coupling
- **Water Hose:** 3/4 with clack, 7 m
- **Spray Gun:** Turnable, Ø 25 mm, Nozzle 14 mm
- **Power Cable:** 3\*4 mm<sup>2</sup> TTR, 20 m
- **Mixing Shaft**
- **2 x Cleaning Ball 30 mm**
- **Round File**
- **6 cm Scraper**
- **Wire Brush**
- **Utility Knife**
- **Manual Rotor Removal Apparatus**

# TURBOMIX PLUS PLASTER MACHINE



# TURBOMIX



+90 216 471 47 97



info@turbomix.com.tr



Ferhatpaşa Mah. G.9 Sk. No:20  
34888 Ataşehir / İstanbul / Turkey



www.turbomix.com.tr