

STATOR
ROTOR



CATALOG



- TURBOMIX GLOBAL -

QUALITY

We have been providing good service for many years with our 100% international products and world class machine and spare parts quality as a plastering machine manufacturer.

Turbomix embraces the highest standards in areas such as quality, environmental protection, occupational health, and customer satisfaction in the plastering machines it produces. As a concrete demonstration of this approach, its international certifications demonstrate its reliability and professionalism in the sector.



CE



ISO 10002:2018



ISO 9001:2015



ISO 45001:2018



ISO 14001:2015

TECHNICAL SPECIFICATIONS

- **Capacity (400 rpm):** 22 l/min
- **Capacity (200 rpm):** 11 l/min
- **Max. grain size:** 3 mm
- **Pompalama Basıncı:** 30 bar
- **Pumping pressure:** 75
- **Stator length:** 270 mm
- **Rotor length:** 320 mm
- **Diameter:** 89 mm



SKU: 11-01-1028

TURBOMIX D6-3 STATOR ROTOR

TECHNICAL SPECIFICATIONS

- **Capacity (400 rpm):** 27 l/min
- **Capacity (200 rpm):** 14 l/min
- **Max. grain size:** 3 mm
- **Pumping pressure:** 30 bar
- **Rubber hardness:** 75
- **Stator length:** 270 mm
- **Rotor length:** 320 mm
- **Diameter:** 89 mm



SKU: 11-01-1029

TURBOMIX D7-2.5 ROTOR STATOR

TECHNICAL SPECIFICATIONS

- **Capacity (400 rpm):** 32 l/min
- **Capacity (200 rpm):** 16 l/min
- **Max. grain size:** 3 mm
- **Pompalama Basıncı:** 30 bar
- **Pumping pressure:** 75
- **Stator length:** 270 mm
- **Rotor length:** 320 mm
- **Diameter:** 89 mm



SKU: 11-01-1030

TURBOMIX D8-2 STATOR ROTOR

TECHNICAL SPECIFICATIONS

- **Capacity (400 rpm):** 70 l/min
- **Capacity (200 rpm):** 35 l/min
- **Max. grain size:** 6 mm
- **Pumping pressure:** 25 bar
- **Rubber hardness:** 75
- **Stator length:** 535 mm
- **Rotor length:** 620 mm
- **Diameter:** 101 mm



SKU: 10-01-1324

TURBOMIX 2L6 STATOR ROTOR

TECHNICAL SPECIFICATIONS

- **Capacity (400 rpm):** 140 l/min
- **Capacity (200 rpm):** 70 l/min
- **Max. grain size:** 6 mm
- **Pompalama Basıncı:** 25 bar
- **Pumping pressure:** 75
- **Stator length:** 535 mm
- **Rotor length:** 620 mm
- **Diameter:** 101 mm



SKU: 10-01-1325

TURBOMIX 2L6 PLUS STATOR ROTOR

TECHNICAL SPECIFICATIONS

- **Capacity (400 rpm):** 140 l/min
- **Capacity (200 rpm):** 70 l/min
- **Max. grain size:** 6 mm
- **Pumping pressure:** 25 bar
- **Rubber hardness:** 75
- **Stator length:** 535 mm
- **Rotor length:** 620 mm
- **Diameter:** 101 mm



SKU: 10-01-1326

TURBOMIX 2L6 PLUS WITH CLAMP STATOR ROTOR



TURBOMIX



+90 543 310 95 95



info@turbomixmachinery.com



Ferhatpaşa Mah. G.9 Sk. No:20
34888 Ataşehir / İstanbul / Türkiye



www.turbomixmachinery.com